CHEMPOIL

Products > Gear oils and transmission fluids > Automatic transmission fluids > CHEMPIOIL Multi ATF JWS 3309



8904 CHEMPIOIL MULTI ATF JWS 3309

A universal all-season high-viscosity synthetic transmission fluid (ATF) for automatic gearboxes. It was specially developed for all modern automatic gearboxes (manual or sequential modes, electronic control, etc.) equipped with and without a hydraulic converter lock-up. It is also compatible with old-generation automatic gearboxes, hydraulic power steering systems, ship reversing gears, hydrostatic transmissions, hydraulic/mechanical systems in which the use of fluids that correspond to Dexron (except Dexron VI) or Mercon standards is prescribed.

It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy. It was developed on the basis of the requirements set by the company AISIN WARNER.

Product properties:

- The highest-quality low-viscosity synthetic base with a consistent high viscosity index in combination with a multifunctional additive package preserves all its properties in a wide range of temperatures: it ensures good lubricating properties at low (-45°C) temperatures in winter and ensures a stable oil film under extreme loads and high temperatures in summer;
- The high-technology combination of additives ensures good antifriction properties for gear couplings and required friction properties for friction elements thus ensuring a significant fuel economy, a continuous and smooth transmission shift and an extended service life of all transmission elements. It ensures a coordinated and smooth operation of the clutch. It prevents scuffing:
- It has an increased thermal-oxidative and chemical stability and resistance to the high-temperature thermal degradation throughout the entire service life. It allows reducing lacquering, formation of sludge, soot and other carbon deposits,

increasing the time between oil changes and ensuring the durability of transmission components thus reducing the equipment maintenance costs;

- It protects metal parts from ferrous and non-ferrous alloys (especially radiators) from corrosion when both in and not in operation;
- It effectively resists aeration and foam formation;
- It ensures a compatibility with all sealing materials, prevents them from swelling, hardening and shrinking thus allowing reducing the costs for spare parts and prevents leakages. It effectively protects fluoroelastomer seals of heavy equipment;
- It reduces noise.

It is recommended for automatic gearboxes produces by American: GM, FORD, CHRYSLER, etc., Asian: HYUNDAI/KIA, MITSUBISHI, NISSAN, SSANGYONG, SUBARU, TOYOTA, etc. and European manufacturers: BMW, CITROEN, FIAT, MB, VOLVO, PEUGEOT, RENAULT, etc.

Colour: red

Comply with the manufacturer's instructions provided in the user's manual!

Corresponds with requirements / specifications / products:

Specifications:

JASO M315 Type 1A

Approval:

Recommendation:

AISIN WARNER JWS 3309

ALLISON C3

ALLISON C4

VOLKSWAGEN G 052 025-A2

VOLKSWAGEN G 052 162-A1

VOLKSWAGEN G 052 990-A1

VOLKSWAGEN G 052 990-A2

VOLKSWAGEN G 055 025-A1

VOLKSWAGEN G 055 025-A2

BMW 7045E (3 Series)

BMW ETL-8072B (5 Series)

BMW LA2634

BMW LT71141 (ZF 5 Speed)

BMW 83 22 0 403 248

BMW 83 22 2 163 514

BMW 83 22 9 407 765 (LA 2634)

BMW 83 22 9 407 807

CHRYSLER ATF+3

CHRYSLER ATF+4

DAIHATSU ALUMIX ATF MULTI

FORD Mercon V

FORD Mercon SP

FORD Mercon LV

FORD ATF Type F

GM Dexron II

GM Dexron II D

GM Dexron II E

GM Dexron III F

GM Dexron III G

GM Dexron III H

HONDA ATF-Z1 (not for CVT)

HONDA ATF DW-1

HYUNDAI ATF SP-II

HYUNDAI ATF SP-III

KIA ATF SP-II

KIA ATF SP-III

IDEMITSU K17-Jaguar X Type 2001-2005

JATCO ATF

JATCO 3100 PL085

MAN 339F

MAN 339 V1

MAN 339 V2

MAN 339 Z1

MAN 339 Z2

MAZDA ATF M-III

MAZDA ATF-MV

MB 236.1

MB 236.2

MB 236.3

MB 236.5

.

MB 236.6

MB 236.7

MB 236.9

MB 236.10

MB 236.11

MITSUBISHI DIAMOND SP-II

MITSUBISHI DIAMOND SP-III

MOPAR AS68RC

NISSAN Matic D

NISSAN Matic J

NISSAN Matic K

PORSCHE JWS 3309

SUBARU ATF-5

SUBARU ATF-HP

SUZUKI 3314

SUZUKI 3317

SUZUKI 2384K

SUZUKI ATF OIL

SUZUKI ATF OIL Special

SSANGYONG DSIH 6P805

TOYOTA ATF Type T

TOYOTA ATF Type T-II

TOYOTA ATF Type T-III

TOYOTA ATF Type T-IV

INFINITI Matic D

INFINITI Matic J

INFINITI Matic K

VOITH H 55.6335.XX (G607)

VOLVO 97340

VOLVO 97341

ZF TE-ML 03D

ZF TE-ML 04D

ZF TE-ML 11B

ZF TE-ML 14A

ZF TE-ML 14B

ZF TE-ML 16L

ZF TE-ML 17

NISSAN N402 (JATCO FWD)

Others TEXACO N402 (JATCO FWD)

LEXUS ATF Type T

LEXUS ATF Type T-II

LEXUS ATF Type T-III

LEXUS ATF Type T-IV

Volume / weight

1L (CH8904-1) 4L (CH8904-4) 20L (CH8904-20) 60L (CH8904-60) 208L (CH8904-DR) 1000L (CH8904-IBC)