



9502 CHEMPIOIL SUPER SL 10W-40

Universal all-season engine oil of economy class on a hydrosynthetic basis for gasoline and diesel engines, both new and "old" brands and with a large mileage. Developed on the basis of the requirements of European manufacturers.

Product Properties:

- The latest generation hydrosynthetic base with an extended range of viscosity-temperature properties ensures efficient operation of the engine in all operating modes: cold start, urban mode, highway mode, as well as under increased load (when driving off-road, uphill, driving with a trailer, maximum load) and at high ambient temperatures;
- Does not lose its properties when using fuel of variable quality (with a sulfur content of up to 500 ppm) due to a large reserve of the base number (TBN);
- The hydrosynthetic base, combined with the latest additive package, preserves the engine's power parameters throughout the entire replacement interval;
- Provides good anti-wear and anti-friction properties, which, in combination with good pumpability, significantly increases the service life of the engine even in "Start-stop" driving modes and during cold start;
- Due to its excellent detergent-dispersing properties and the highest thermal-oxidative stability, it effectively combats all types of deposits and keeps engine parts clean throughout the entire replacement interval;

It is intended for gasoline and diesel engines of a wide fleet of cars (passenger cars, light SUVs, minibuses and light trucks) of European and other manufacturers.

Recommended for use in engines of Daimler, VW cars that have additional requirements for engine oils (according to the above specifications).

The oil is not suitable for use in heavy trucks and similar vehicles!

Corresponds with requirements / specifications / products:

Specifications:

SAE 10W-40

Recommendation:

API SL/CH-4

ACEA A3/B4

VOLKSWAGEN 502 00

MB 229.1

VOLKSWAGEN 505 00

Volume / weight

5L (CH9502-5)